

# Hazardous Substances Risk Assessment

● Victoria

● New South Wales

● Queensland



**SHANNON TOWER PTY. LTD.** EST 1992

Trading as **Brick N Pavé**  
A.C.N. 056 378 575 A.B.N. 69 056 378 575

Toll Free: 1300 729 758  
Web: www.bricknpave.com.au



**Hazardous Substance:**

Product Name	Quantity Stored	Location/s	Location of SDS	Supplier Details:	Date for Assessment	Controls	Risk Assessment
Polyaspartic 85 RC Part B	Up to 20 Boxes (Depot) / Up to 10 Boxes (Vehicles)	Depot/ Vehicle	Depot/ Vehicle	As below:	01.01.2022	PPE as per SDS	Yes

*All Assessments must not be older than 5 years.*

*Where the product is identified as a Hazardous Substance, an SDS and a completed Risk Assessment must be kept in a register.*

**Supplier:**

Product:	Supplier Name:	Phone Number:
Polyaspartic 85 RC Part B	E2U Epoxy 2U Australia	1800 003 832

**Risk Assessment:**

Date of Assessment:	Name:	Position:
30 <sup>th</sup> June 2023	Brendan Evans	QLD Manager
Date for Re-Assessment		
30 <sup>th</sup> June 2024		

Risk Assessment		
SDS Reviewed / Available	<input type="checkbox"/> Yes	<input type="checkbox"/> No
How is the Substance Used?	Part B of a two-part epoxy primer used in application of coloured surfacing to concrete surfaces.	

Risks Involved with using the Substance:	Irritation to eyes, mouth, lungs, stomach. Can cause health problems if ingested in large amounts. Drying of skin. Respiratory problems possible.	
Health Aspects:	Potential chemical burns to eye/skin/hands/irritation. Potential skin irritation if exposed to long times or in large volumes. May cause nausea, vomiting, swelling, blisters. Potential to cause permanent lung damage if inhaled for long periods.	
Assessment of the Risk:	<input type="checkbox"/> High <input checked="" type="checkbox"/> Medium <input type="checkbox"/> Low	
Necessary Controls:	Must be used in a well-ventilated area. Use protective goggles, dust mask, or full-face shield fitted with filter to AS. Heavy duty rubber gloves if skin is dry, cracked, split, or sensitive. Protective clothing to shield skin from contact. Safety or rubber boots.	
Approximate Quantity:	Up to 20 Boxes (Depot) / Up to 10 Boxes (Vehicles)	
Storage Requirements:	Store well in well-ventilated areas. Keep containers sealed at all times when not in use. Protect from physical damage. Keep away from ignition sources. Dispose of unused material safely.	
Required Safety Phrases:	In case of contact, do not induce vomiting, flush eyes with water continually, remove person/s from source. Immediately seek medical help. Give oxygen if possible. Contact poison control centre if medical help is unavailable. Transport patient to nearest medical facility ASAP if any contact with this chemical deemed to be dangerous is experienced.	
Monitoring Requirements:	Monitor workers for correct use during works. Use shifts to avoid inhalation of product over the allowed limits.	
Health Surveillance:	<input type="checkbox"/> Yes	<input checked="" type="checkbox"/> No