

ADVANTAGES

The E2U one day single colour system is industry leading in its speed of application and physical properties; usually, one of these things comes at the cost of the other. But not in this case.

By combining E2Us unique 6150RC Epoxy with our equally class leading Polyaspartic85 as a top coat your floor will have the best adhesion to your substrate, the advantage of an epoxy, with the superior speed and strength of a polyaspartic topcoat.

Depending on the condition of the substrate, this system will clean up a workshop, hangar, or garage floor quickly and easily when aesthetics are less of a concern. However, the absolute best results will require extra prep work and repairs as this system does not have the ability to hide minor flaws, unlike the flake system.

FEATURES

- +High gloss and build
- +4x the abrasion resistance of epoxy
- +Non-Yellowing UV stable
- +Chemical resistant
- +Low odour, none immediately after application
- +VOC compliant
- +Solvent free
- +Can cure just above freezing temperature
- +Will not support the growth of bacteria or fungus
- +Will handle forklift turning and traffic



APPLICATIONS

- | | | |
|---------------------|-------------------------|------------------------|
| +Pharmaceutical | +Clean Rooms | +Veterinary Facilities |
| +Food Prep/Kitchens | +Showrooms | +Bath/Changing Rooms |
| +Garage Floors | +Schools | +Ramps/Walkways |
| +Laboratories | +Health Care Facilities | +Manufacturing Plants |
| +Basements | +Loading Docks | +Hangars |
| +Kennels | +Car Wash Facilities | +Driveways |

